

If **YOU** specify, distribute, purchase, fabricate or install steel gratings,

YOU have a responsibility to provide compliant products to the latest specification.



Specification to: BS4592-0:2006+A1:2012

To be used where the working platform or walkway is above a place where people are working (as opposed to people passing under it occasionally). The maximum openings shall not permit the passage of a 20mm diameter sphere.

Typically used on walkways above machinery and permanent working areas, where the risk to personnel from large objects, falling from above, is critical.

Specification to: BS4592-0:2006+A1:2012

To be used where the working platform or walkway is above a place where people pass through occasionally, the maximum openings shall not permit the passage of a 35mm diameter sphere.

Typically used on maintenance access, industrial plants, un-manned substation modules, data centres, where site access is limited and occasional.

Utility Grating High Grating

Specification to: BS4592-0:2006+A1:2012

To be used where there is no risk of personnel passing below the working platform or walkway.

Typically used on ground level shallow trenches, above water channels in treatment works or placed on solid floors to elevate walking areas from contaminants.

Contact the Technical Team at Belfast +44 (0) 28 90454599 or Ashbourne +353 (01) 802 7173

Belfast: 103 Airport Road West, Belfast, Co. Down BT3 9ED Ashbourne: Unit 1 & 2 Greene Park, Ratoath Road, Ashbourne, Co. Meath A84 XD98









Email: info@ridgeway-online.com Website: www.ridgeeway-online.com



